

## draincam SL50

### operational:

- tubes of DN 70 to DN 300
- bends of DN 100 / 87 °

### specifications:

- of stainless steel  $\varnothing 50\text{mm}$ , waterproof till 4 bar
- lightning ring with 40 pc.  $\varnothing 3\text{ mm}$  brilliant white LED's
- objektive with 97° viewing angle, 2.1/F2.0
- camera modul: 1/4", 1 Lux, 542(H) x 586(V), 380 TVL
- reel of steel frame galvanize
  - slip-ring
  - push rod with wire  $\varnothing 9,0\text{ mm}$  / 80 m
  - control unit of aluminum case, with integrated supply distribution and camera / light operation
- LCD Monitor 5,6"
  - Auflösung: (960 x 234)
  - Helligkeit: (350) cd / m<sup>2</sup>
  - Kontrast: 350:1
- power supply:
  - AC 100 / 240 V, 47 / 63 Hz, 30 W
  - extern +12V

### options:

- upright picture unit
- push rod with wire  $\varnothing 9,0\text{ mm}$  / 100 m / 120m
- meter display, resolution 0,1m / 0,01m
- data and meter display
- software

### accessories:

- 5,6"LCD Monitor+DVR+alu chase
- LCD Monitor 8" oder 10.4" in chase
- 12V battery
- adapter:
  - skid  $\varnothing 80$ , from DN 100
  - rollskid  $\varnothing 112$ , from DN 125
  - rollskid  $\varnothing 137$ , ab DN 150
  - rollskid  $\varnothing 180$ , ab DN 200
- pushrod

### dimensions:

- w: 82 cm d: 32 cm h: 93 cm
- weight: ca. 26 kg

